H-Tech LED Shoebox Light





Parameter


- Philips Lumileds LED source. High luminous efficiency and long life.
- High efficiency LED driver ,the wide input voltage is AC100-277V
- Light efficiency>90LM/W, CRI >80
- Heat pipe with FIN cooling design, better cooling, LED Tj<85 $^{\circ}$ C
- The products got the RoHS , UL&CUL ,FCC,DLC certification
- Excellent lampshape design, greatly improve the light utilization and evenness

Туре	CH-XH-200W	Input Voltage	100-277V/50-60Hz
Light Source	PHILIPS Lumileds	Dimming	NO
Power	200W	Power Factor	0.95
Beam Angle	120°	THD	<15%
Luminous Flux	More than 18000LM	Connection	3 Polors
Lumen Efficacy	Up to 90LM/W	Warranty	5 Years
Color Temperature	3000-5000K	IP Rating	IP65
Operating Temp.	-30-45 ℃	Replace For	400W(HID)
CRI	Ra75	Certification	UL.DLC.FCC.ROHS
Driver	MeanWell	UL Number	E472052

Outdoor and Industry LED Lighting E-mail:info@cltlledsolutions.com



Light Distribution Curve



Application

LED gas station Light series can be widely used in sport place, Urban roads, Industrial areas,

Residential areas, Sidewalks, Parking lot, Schools, Gardens and etc.




Outdoor and Industry LED Lighting E-mail:info@cltlledsolutions.com

Web:www.cltlledsolutions.com



Temperature Compensation



Control module activates at 45C. L70 output reached at 55C.


Continuous operation after 55C with increased compensation.

CSA certification valid to 55C only.

Chart accurate for Standard Output versions only.

• Net weight: 11.50Kg

Unit: mm



Packing details

Model	Meas	Qty	Net weight
CH-XH-200W	654*420*277mm	1pcs/carton	11.8kg


Outdoor and Industry LED Lighting E-mail:info@cltlledsolutions.com

Web:www.cltlledsolutions.com

H-Tech LED Shoebox Light



Installation



Outdoor and Industry LED Lighting E-mail:info@cltlledsolutions.com

Web:www.cltlledsolutions.com